





RCJ90-XL

Flanged housing unit

Housing units RCJ, four-bolt flanged housing units, cast iron, eccentric locking collar, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|                 |           |                                   |
|-----------------|-----------|-----------------------------------|
| d               | 90 mm     | Bore diameter                     |
| L               | 235 mm    | Flange width                      |
| U               | 70,3 mm   | Total height unit                 |
| C <sub>r</sub>  | 109.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 79.000 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 3.650 N   | Fatigue load limit, radial        |
| ≈m              | 8,88 kg   | Masa                              |

Mounting dimensions

|   |        |                          |
|---|--------|--------------------------|
| J | 187 mm | Distance fixing bore     |
| N | 23 mm  | Fixing bore              |
| n | 4      | Number of screwing holes |



Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 39,8 mm | Height housing                    |
| A <sub>1</sub> | 22 mm   | Thickness of flange               |
| A <sub>2</sub> | 23,8 mm | Distance raceway                  |
| V              | 200 mm  | Shoulder diameter housing         |
| Q              | M6      | Connection thread for lubrication |
| d <sub>3</sub> | 118 mm  | Outside diameter locking device   |

Additional information

|               |                     |
|---------------|---------------------|
| 1             | Number of housings  |
| CJ18          | Housing             |
| GE90-XL-KRR-B | Bearing designation |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |