





RCJT20-XL-N

Flanged housing unit

Housing units RCJT, two-bolt flanged housing units, cast iron, eccentric locking collar, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	61 mm	Flange width
H	112 mm	Height flange
U	45,6 mm	Total height unit
C _r	13.600 N	Basic dynamic load rating, radial
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	345 N	Fatigue load limit, radial
≈m	0,48 kg	Masa

Mounting dimensions

J	90 mm	Distance fixing bore
N	11,5 mm	Fixing bore
n	2	Number of screwing holes
W	3 mm	Width of flats



Dimensions

A	28 mm	Height housing
A 1	10 mm	Thickness of flange
A 2	19 mm	Distance raceway
B 1	43,7 mm	Locking collar total width
V	61 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d 3	33 mm	Outside diameter locking collar

Additional information

1	Number of housings
CJT04	Housing
GE20-XL-KRR-B	Bearing designation
KASK04	Protecting cap

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.