



**RCJTHOC25-VA-FD** 

Flanged housing unit

Informacje techniczne

Twoja aktualna wersja produktu

|                             |    |                               |
|-----------------------------|----|-------------------------------|
| Material                    | VA | Stainless Steel               |
| Corrosion resistant bearing | VA | Corrosion-resistant VA design |

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 25 mm    | Bore diameter                     |
| L               | 63 mm    | Flange width                      |
| H               | 130 mm   | Height flange                     |
| U               | 50,9 mm  | Total height unit                 |
| C <sub>r</sub>  | 12.200 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.500 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 550 N    | Fatigue load limit, radial        |
| ≈m              | 0,89 kg  | Masa                              |

Mounting dimensions

|   |       |                      |
|---|-------|----------------------|
| J | 99 mm | Distance fixing bore |
| N | 16 mm | Fixing bore          |
| W | 3 mm  | Width of flats       |



Dimensions

|                |         |                                 |
|----------------|---------|---------------------------------|
| A              | 42,7 mm | Height housing                  |
| A <sub>1</sub> | 22,7 mm | Thickness of flange             |
| A <sub>2</sub> | 28,7 mm | Distance raceway                |
| Y              | 12,7 mm | Distance housing base           |
| d <sub>3</sub> | 42 mm   | Outside diameter locking collar |

Additional information

|                   |                     |
|-------------------|---------------------|
| GEH.CJTH05-VA-NAT | Housing             |
| OCE25-DC-B-VA-FD  | Bearing designation |
| KASK05-VA-G-NAT   | Protecting cap      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |