



RCJTY40-TV-VA

Flanged housing unit

Flanged housing unit RCJTY...-TV-VA

Informacje techniczne

Twoja aktualna wersja produktu

Material	TV	Plastic
----------	----	---------

Main Dimensions & Performance Data

d	40 mm	Bore diameter
L	100 mm	Flange width
H	175 mm	Height flange
U	51,7 mm	Total height unit
C _r	31.500 N	Basic dynamic load rating, radial
C _{0r}	18.900 N	Basic static load rating, radial
C _{ur}	930 N	Fatigue load limit, radial
C _{0r G}	14.900 N	Load carrying capacity (housing)
≈m	0,874 kg	Masa

Mounting dimensions

J	144 mm	Distance fixing bore
N	14 mm	Fixing bore
W	4 mm	Width across flats
n	2	Number of screwing holes



Dimensions

A	37,5 mm	Height housing
A ₁	20 mm	Thickness of flange
A ₂	21,5 mm	Distance raceway

Additional information

1	Number of housings
GEHCJT08-TV	Housing
GYE40-XL-KRR-B-FA107-VA	Bearing designation
KASK08	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.