


RCRB25/57-XL-FA106

Radial insert ball bearing

Radial insert ball bearings RCR, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	57,3 mm	Outside diameter
C	19,8 mm	Width, outer ring
B 1	31 mm	Locking collar total width
C r	14.000 N	Basic dynamic load rating, radial
C 0r	7.800 N	Basic static load rating, radial
C ur	370 N	Fatigue load limit, radial
	1.400 N	Load carrying capacity (rubber interliner)
≈m	0,202 kg	Masa

Dimensions

C 2	17,5 mm	Width outside profile of rubber interliner
S 1	23,5 mm	Distance raceway to locking collar
D 2	44,5 mm	Flange diameter rubber interliner
d 3	37,5 mm	Outside diameter locking collar/locknut
P	9,8 mm	Distance raceway of rubber interliner to face side



Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Additional information

	RAE25-XL-NPP-FA106	Bearing designation
Shore A	70 °	Hardness rubber interliner