


**RNA22/6-2RSR**

Yoke type track roller

Yoke type track rollers RNA22...-2RSR, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly, without inner ring, without axial guidance of the outer ring, lip seal radial sealing action on both sides, inner ring can be mounted separately

Informacje techniczne



Twoja aktualna wersja produktu

|                    |      |                        |
|--------------------|------|------------------------|
| Sealing            | 2RSR | Lip seal on both sides |
| Outer ring profile | R500 | R500                   |

Main Dimensions & Performance Data

|                   |             |                                       |
|-------------------|-------------|---------------------------------------|
| D                 | 19 mm       | Outside diameter                      |
| F <sub>w</sub>    | 10 mm       | Under roller diameter                 |
| C                 | 11,8 mm     | Width, outer ring                     |
| C <sub>r w</sub>  | 3.350 N     | Basic dynamic load rating, radial     |
| C <sub>0r w</sub> | 3.650 N     | Basic static load rating, radial      |
| C <sub>ur w</sub> | 495 N       | Fatigue load limit, radial            |
| n <sub>D G</sub>  | 9.000 1/min | Speed on permanent grease lubrication |
| ≈m                | 13,905 g    | Masa                                  |

Dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| D <sub>1 min</sub> | 15,15 mm | Minimum mounting dimension           |
| r <sub>min</sub>   | 0,3 mm   | Minimum chamfer dimension            |
| R                  | 500 mm   | Radius of outer ring outside profile |



### Właściwości



Obciążenie promieniowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne