


RNA4848-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	265 mm	Under roller diameter
D	300 mm	Outside diameter
B	60 mm	Width
C _r	400.000 N	Basic dynamic load rating, radial
C _{0r}	1.080.000 N	Basic static load rating, radial
C _{ur}	153.000 N	Fatigue load limit, radial
n _G	1.780 1/min	Limiting speed
n _G Grease	1.070 1/min	Limiting speed for grease lubrication
n _{gr}	980 1/min	Reference speed
m	5,394 kg	Masa



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
C	60 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy