




RNA4902-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	the aid of the bearing frequency calculator, you can determine this by inputting the geometrical data.	With
Coating	Without	
Sealing	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F_w	20 mm	Under roller diameter
D	28 mm	Outside diameter
B	13 mm	Width
C_r	12.000 N	Basic dynamic load rating, radial
C_{0r}	13.600 N	Basic static load rating, radial
C_{ur}	2.470 N	Fatigue load limit, radial
n_G	21.100 1/min	Limiting speed
$n_{G Grease}$	12.600 1/min	Limiting speed for grease lubrication
n_{gr}	12.000 1/min	Reference speed
$\approx m$	21,9 g	Masa



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	13 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

G20X28X4	Sealing ring
SD20X28X4	Sealing ring 2

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy