



**RSHEOC25-VA-FD**

Plummer block housing unit

Informacje techniczne

Twoja aktualna wersja produktu

|          |    |                 |
|----------|----|-----------------|
| Material | VA | Stainless Steel |
|----------|----|-----------------|

Main Dimensions & Performance Data

|      |          |                                   |
|------|----------|-----------------------------------|
| d    | 25 mm    | Bore diameter                     |
| L    | 83 mm    | Length total                      |
| H 2  | 68 mm    | Height                            |
| U    | 37,2 mm  | Total width unit                  |
| C r  | 12.200 N | Basic dynamic load rating, radial |
| C 0r | 6.500 N  | Basic static load rating, radial  |
| C ur | 550 N    | Fatigue load limit, radial        |
| ≈m   | 0,65 kg  | Masa                              |

Mounting dimensions

|     |           |                      |
|-----|-----------|----------------------|
| J   | 50,8 mm   | Distance fixing bore |
| K   | 3/8-16UNC | Thread fixing bore   |
| H 3 | 13 mm     | Thread length        |

Dimensions

|     |         |                                       |
|-----|---------|---------------------------------------|
| H   | 36,5 mm | Distance shaft axis                   |
| A   | 30 mm   | Width (base)                          |
| S 1 | 22,2 mm | Distance of raceway to locking collar |



Additional information

|                  |                     |
|------------------|---------------------|
| GEH.SHE05-VA-NAT | Housing             |
| OCE25-DC-B-VA-FD | Bearing designation |
| KASK05-VA-G-NAT  | Protecting cap      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |