



RSL182213-A-XL


Cylindrical roller bearing

Cylindrical roller bearing RSL18.-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	65 mm	Bore diameter
E _w	106,25 mm	Outer envelope circle
B	31 mm	Width
C _r	198.000 N	Basic dynamic load rating, radial
C _{0r}	210.000 N	Basic static load rating, radial
C _{ur}	39.500 N	Fatigue load limit, radial
n _G	4.200 1/min	Limiting speed
≈m	0,925 kg	Masa

Mounting dimensions

d _{a min}	82,3 mm	Minimum diameter shaft shoulder
X	22 mm	Raceway width

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
d ₁	82,3 mm	Maximum rib diameter inner ring
T _K	91,25 mm	Pitch circle



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia