




RSL182220-A

Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
E _w	162,81 mm	Outer envelope circle
B	46 mm	Width
C _r	390.000 N	Basic dynamic load rating, radial
C _{0r}	510.000 N	Basic static load rating, radial
C _{ur}	74.000 N	Fatigue load limit, radial
n _G	2.300 1/min	Limiting speed
≈m	3,35 kg	Masa

Mounting dimensions

d _{a min}	127,5 mm	Minimum diameter shaft shoulder
X	34 mm	Raceway width



Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
d_1	127,5 mm	Maximum rib diameter inner ring

T_K	140,81 mm	Pitch circle
-------	-----------	--------------

Temperature range

T_{min}	-30 °C	Operating temperature min.
-----------	--------	----------------------------

T_{max}	120 °C	Operating temperature max.
-----------	--------	----------------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia