



RSL182308-A-XL


Cylindrical roller bearing



Cylindrical roller bearing RSL1823..-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
E _w	83,12 mm	Outer envelope circle
B	33 mm	Width
C _r	170.000 N	Basic dynamic load rating, radial
C _{0r}	153.000 N	Basic static load rating, radial
C _{ur}	29.000 N	Fatigue load limit, radial
n _G	5.800 1/min	Limiting speed
≈m	0,728 kg	Masa

Mounting dimensions

d _{a min}	50,5 mm	Minimum diameter shaft shoulder
X	24 mm	Raceway width

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
d ₁	50,5 mm	Maximum rib diameter inner ring
T _K	67,12 mm	Pitch circle



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia