




RSL182310-A

Cylindrical roller bearing

Cylindrical roller bearing RSL1823, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant Cage A
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	50 mm	Bore diameter
E _w	98,72 mm	Outer envelope circle
B	40 mm	Width
C _r	205.000 N	Basic dynamic load rating, radial
C _{0r}	215.000 N	Basic static load rating, radial
C _{ur}	33.500 N	Fatigue load limit, radial
n _G	4.200 1/min	Limiting speed
≈m	1,168 kg	Masa

Mounting dimensions

d _{a min}	68 mm	Minimum diameter shaft shoulder
X	28 mm	Raceway width

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
d ₁	68,3 mm	Maximum rib diameter inner ring
T _K	79,72 mm	Pitch circle



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia