



IMAGE
COMING SOON




RUKS35-D-A-H-SR

Braking/clamping element

Clamping element RUKS...-D-A-H-SR, for linear recirculating roller bearing and guideway assembly, oil connector on side

Informacje techniczne



Twoja aktualna wersja produktu


Size	35	
Version	D	
Internal design	A	
Carriage design	H	High carriage
Oil feed	SR	Oil connector on side

Main Dimensions & Performance Data

H	55 mm	Height sytem
B	68 mm	Width clamping element
L	134,3 mm	Length of clamping element
≈m	2,3 kg	Masa



Mounting dimensions



J _B	50 mm	Hole pattern width
A ₃	39,5 mm	Mounting dimension oil connector
L ₁	113 mm	Length saddle plate
J _{L1}	50 mm	Hole pattern lengthwise
J _{L5}	38 mm	Distance
N _{2 max}	6 mm	Max diameter lubrication hole adjacent constr
H ₁	6,8 mm	Space (system)
H ₃	42 mm	
T ₇	10 mm	Depth thread
H ₉	20,4 mm	
G ₂	M8	Size thread above for DIN ISO 4762-12.9
M G ₂	41 Nm	Tightening torque above

Related products

TSX35-E; TSX35-F	Suitable guideway
RUE35-E; RUE35-F	Suitable system