



IMAGE  
COMING SOON**RUKS55-D-A-H-SO**

Braking/clamping element

Clamping element RUKS...-D-A-H-SO, for  
linear recirculating roller bearing and  
guideway assembly, oil connector on top

## Informacje techniczne




## Twoja aktualna wersja produktu

|                 |    |                     |
|-----------------|----|---------------------|
| Size            | 55 |                     |
| Version         | D  |                     |
| Internal design | A  |                     |
| Carriage design | H  | High carriage       |
| Oil feed        | SO | Oil feed from above |

## Main Dimensions &amp; Performance Data

|    |          |                            |
|----|----------|----------------------------|
| H  | 80 mm    | Height sytem               |
| B  | 98 mm    | Width clamping element     |
| L  | 186,3 mm | Length of clamping element |
| ≈m | 6,55 kg  | Masa                       |



Mounting dimensions

|         |         |                                               |
|---------|---------|-----------------------------------------------|
| J B     | 75 mm   | Hole pattern width                            |
| L 1     | 163 mm  | Length saddle plate                           |
| J L1    | 75 mm   | Hole pattern lengthwise                       |
| J L5    | 50,5 mm | Distance                                      |
| N 2 max | 6 mm    | Max diameter lubrication hole adjacent constr |
| H 1     | 11 mm   | Space (system)                                |
| H 3     | 62 mm   |                                               |
| T 7     | 15 mm   | Depth thread                                  |
| G 2     | M12     | Size thread above for DIN ISO 4762-12.9       |
| M G 2   | 140 Nm  | Tightening torque above                       |

Related products

|                  |                   |
|------------------|-------------------|
| TSX55-E; TSX55-F | Suitable guideway |
| RUE55-E; RUE55-F | Suitable system   |