



IMAGE
COMING SOON



RUKS55-D-A-SO

Braking/clamping element

Clamping element RUKS...D-A-SO,for linear
recirculating roller bearing and guideway
assembly, oil connector on top


Informacje techniczne


Twoja aktualna wersja produktu

Size	55	
Version	D	
Internal design	A	
Oil feed	SO	Oil feed from above

Main Dimensions & Performance Data

H	70 mm	Height sytem
B	138 mm	Width clamping element
L	186,3 mm	Length of clamping element
≈m	6,96 kg	Masa





Mounting dimensions

J _B	116 mm	Hole pattern width
L ₁	163 mm	Length saddle plate
J _{L1}	95 mm	Hole pattern lengthwise
J _{L2}	70 mm	Hole pattern centre
J _{L5}	40,5 mm	Distance
N _{2 max}	6 mm	Max diameter lubrication hole adjacent constr
H ₁	11 mm	Space (system)
H ₃	32 mm	
T ₇	18 mm	Depth thread
G ₂	M14	Size thread above for DIN ISO 4762-12.9
M _{G 2}	140 Nm	Tightening torque above
K ₃	M12	Size thread below for DIN ISO 4762-12.9
M _{K 3}	140 Nm	Tightening torque below
D ₂	12,5 mm	Through-bore

Related products

TSX55-E; TSX55-F	Suitable guideway
RUE55-E; RUE55-F	Suitable system