



RUS26086

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Informacje techniczne




Twoja aktualna wersja produktu

Size 26086

Main Dimensions & Performance Data

L tot	90 mm	Total length
L	86,4 mm	
B	40 mm	Width
H	26 mm	Height
C	76.000 N	Basic dynamic load rating
C 0	113.000 N	Basic static load rating
≈m	0,5 kg	Masa



Mounting dimensions

L 1	52,8 mm	Mounting dimension
J B	30 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	28 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	63 mm	Minimum support length
L w	14 mm	
H 4	21 mm	
T 5	10,2 mm	
G 1	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	17 Nm	Tightening torque fixing screws
K 3	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	5 Nm	Tightening torque fixing screws
D 2	4,9 mm	
	6 mm	

Related products

VUS26086-A	Adjustment gib
UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail