



RUS26102

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Informacje techniczne




Twoja aktualna wersja produktu

Size 26102

Main Dimensions & Performance Data

L _{tot}	106 mm	Total length
L	102,4 mm	
B	40 mm	Width
H	26 mm	Height
C	95.000 N	Basic dynamic load rating
C ₀	151.000 N	Basic static load rating
≈m	0,6 kg	Masa



Mounting dimensions

L 1	68,9 mm	Mounting dimension
J B	30 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	44 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	79 mm	Minimum support length
L W	14 mm	
H 4	21 mm	
T 5	10,2 mm	
G 1	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	17 Nm	Tightening torque fixing screws
K 3	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	5 Nm	Tightening torque fixing screws
D 2	4,9 mm	
	6 mm	

Related products

VUS26102-A	Adjustment gib
UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail