



RUS38134

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Informacje techniczne



Twoja aktualna wersja produktu

Size 38134

Main Dimensions & Performance Data

L tot 132 mm Total length

L 132,7 mm


B 52 mm Width

H 38 mm Height

C 179.000 N Basic dynamic load rating

C 0 275.000 N Basic static load rating

≈m 1,27 kg Masa



Mounting dimensions

L 1	84,7 mm	Mounting dimension
J B	41 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	51 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	100 mm	Minimum support length
L w	20 mm	
H 4	31 mm	
T 5	14,2 mm	
G 1	M8	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	41 Nm	Tightening torque fixing screws
K 3	M6	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	17 Nm	Tightening torque fixing screws
D 2	6,9 mm	
	6 mm	

Related products

VUS38134-A	Adjustment gib
UG12553, UGN12553- A, UZ12553, UZN12553-A, UFG6412, UFB7812	Suitable Guide rail