





FAG

S685>N

Deep groove ball bearing

Deep groove ball bearing S68, corrosion-resistant materials, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	5 mm	Bore diameter
D	11 mm	Outside diameter
B	3 mm	Width
C _r	760 N	Basic dynamic load rating, radial
C _{0r}	280 N	Basic static load rating, radial
C _{ur}	17,5 N	Fatigue load limit, radial
n _G	84.000 1/min	Limiting speed
n _{gr}	34.000 1/min	Reference speed
≈m	1,18 g	Masa



Mounting dimensions

$d_{a\ min}$	5,8 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	10,2 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,15 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,15 mm	Minimum chamfer dimension
D_1	9,15 mm	Shoulder diameter outer ring
d_1	6,7 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

f_0	13,9	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Ochrona przed korozją