


SL024936-A-BR-C3

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | A            | Internal Variant A                |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 2            | Double-row design                 |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 180 mm      | Bore diameter                     |
| D               | 250 mm      | Outside diameter                  |
| B               | 69 mm       | Width                             |
| C <sub>r</sub>  | 570.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.200.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 149.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.480 1/min | Limiting speed                    |
| n <sub>gr</sub> | 920 1/min   | Reference speed                   |
| ≈m              | 10,156 kg   | Masa                              |

Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>c min</sub> | 205 mm   | Minimum shaft shoulder               |
| d <sub>a min</sub> | 204,9 mm | Minimum diameter shaft shoulder      |
| D <sub>e min</sub> | 230,5 mm | Minimum diameter of housing shoulder |
| r <sub>a max</sub> | 2 mm     | Maximum recess radius                |



Dimensions

|                    |          |                                 |
|--------------------|----------|---------------------------------|
| r <sub>min</sub>   | 2 mm     | Minimum chamfer dimension       |
| s                  | 4 mm     | Axial displacement              |
| C                  | 34,5 mm  | Distance to lubrication hole    |
| d <sub>1 max</sub> | 204,9 mm | Maximum rib diameter inner ring |
| E                  | 230,5 mm | Raceway diameter outer ring     |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |

Additional information

|           |                             |
|-----------|-----------------------------|
| NNCL4936V | Bearing designation DIN5412 |
|-----------|-----------------------------|

Właściwości

|  |                        |
|--|------------------------|
|  | Obciążenie promieniowe |
|  | Smarowanie smarem      |
|  | Smarowanie olejem      |
|  | Bez uszczelnienia      |