




SL1818/630-E-TB-BR-CN/3L [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing, SL1818.-E-TB
full complement roller set, single row, semi-
locating bearing, 1 rib on outer ring, 2 ribs on
inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	630 mm	Bore diameter
D	780 mm	Outside diameter
B	69 mm	Width
C _r	1.410.000 N	Basic dynamic load rating, radial
C _{0r}	3.150.000 N	Basic static load rating, radial
C _{ur}	285.000 N	Fatigue load limit, radial
n _G	425 1/min	Limiting speed
n _{gr}	260 1/min	Reference speed
m	68 kg	Masa



Mounting dimensions

$d_{a \min}$	680 mm	Minimum diameter shaft shoulder
$d_{c \min}$	680 mm	Minimum shaft shoulder
$D_{a \max}$	725,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	742,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
E	742,5 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
s	7,5 mm	Axial displacement
d_1	680 mm	Maximum rib diameter inner ring
$D_1 \min$	725,6 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe