



SL182220-A-C3

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	180 mm	Outside diameter
B	46 mm	Width
C _r	390.000 N	Basic dynamic load rating, radial
C _{0r}	510.000 N	Basic static load rating, radial
C _{ur}	74.000 N	Fatigue load limit, radial
n _G	2.300 1/min	Limiting speed
n _{gr}	1.700 1/min	Reference speed
≈m	4,98 kg	Masa



Mounting dimensions

$d_{a\ min}$	127,5 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	127,5 mm	Minimum shaft shoulder
$D_{a\ max}$	154 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	163 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum recess radius
E	163,4 mm	Raceway diameter outer ring

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
d_1	127,5 mm	Maximum rib diameter inner ring
$D_1\ min$	154,3 mm	Minimum rib diameter outer ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia