




SL182236-A-BR

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	320 mm	Outside diameter
B	86 mm	Width
C _r	1.180.000 N	Basic dynamic load rating, radial
C _{0r}	1.760.000 N	Basic static load rating, radial
C _{ur}	218.000 N	Fatigue load limit, radial
n _G	1.230 1/min	Limiting speed
n _{gr}	800 1/min	Reference speed
m	28,94 kg	Masa



Mounting dimensions

d a min	232 mm	Minimum diameter shaft shoulder
d c min	232 mm	Minimum shaft shoulder
D a max	279,5 mm	Maximum diameter of housing shoulder
D e min	294 mm	Minimum diameter of housing shoulder
r a max	4 mm	Maximum recess radius
E	294 mm	Raceway diameter outer ring

Dimensions

r min	4 mm	Minimum chamfer dimension
s	7 mm	Axial displacement
d 1	232 mm	Maximum rib diameter inner ring
D 1 min	279,5 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe