



SL182936-B-XL-C5

Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	C5 (Group 5)	Internal clearance larger than C4
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	250 mm	Outside diameter
B	42 mm	Width
C _r	455.000 N	Basic dynamic load rating, radial
C _{0r}	680.000 N	Basic static load rating, radial
C _{ur}	106.000 N	Fatigue load limit, radial
n _G	1.720 1/min	Limiting speed
n _{gr}	1.150 1/min	Reference speed
≈m	6,002 kg	Masa





Mounting dimensions

$d_{a\ min}$	200,7 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	200,5 mm	Minimum shaft shoulder
$D_{a\ max}$	224 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	231,5 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum recess radius
E	231,9 mm	Raceway diameter outer ring

Dimensions

$r_{\ min}$	2 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
d_1	200,7 mm	Maximum rib diameter inner ring
$D_1\ min$	224 mm	Minimum rib diameter outer ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia