




SL182956-TB-BR

Cylindrical roller bearing

Cylindrical roller bearing SL1829..-TB, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	380 mm	Outside diameter
B	60 mm	Width
C _r	910.000 N	Basic dynamic load rating, radial
C _{0r}	1.710.000 N	Basic static load rating, radial
C _{ur}	193.000 N	Fatigue load limit, radial
n _G	940 1/min	Limiting speed
n _{gr}	590 1/min	Reference speed
≈m	19,165 kg	Masa



Mounting dimensions

$d_{a \min}$	314 mm	Minimum diameter shaft shoulder
$d_{c \min}$	314 mm	Minimum shaft shoulder
$D_{a \max}$	348,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	359,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
E	359,5 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
s	3,5 mm	Axial displacement
d_1	314 mm	Maximum rib diameter inner ring
$D_1 \min$	348,5 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe