

STO8-X-TV

Yoke type track roller

Yoke type track rollers STO.., single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and an inner ring, without axial guidance of the outer ring, open, inner ring, outer ring and needle roller and cage assembly can be mounted separately

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	
Outer ring profile	X	Cylindrical profile
Relubrication feature	IR	Via inner ring lubrication hole
Cage	TV	Plastic Cage made from PA66

Main Dimensions & Performance Data

d	8 mm	Bore diameter
D	24 mm	Outside diameter
C	9,8 mm	Width, outer ring
C_{rw}	4.200 N	Basic dynamic load rating, radial
C_{0rw}	5.600 N	Basic static load rating, radial
C_{urw}	800 N	Fatigue load limit, radial
n_{DG}	8.000 1/min	Speed on permanent grease lubrication
≈m	27,18 g	Masa

Dimensions

B	10 mm	Width, inner ring
E	15 mm	Raceway diameter outer ring
r_{min}	0,3 mm	Minimum chamfer dimension
F	12 mm	Raceway diameter inner ring
R	500 mm	Radius of outer ring outside profile

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Właściwości

- Obciążenie promieniowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje