




SX011848-A

Crossed roller bearing

Crossed roller bearingsdimension series 18 to
DIN 616

Informacje techniczne



Main Dimensions & Performance Data

d _i	240 mm	Bore Diameter
	0,005 mm	Bore diameter upper tolerance
	-0,024 mm	Bore diameter lower tolerance
D _a	300 mm	Outside Diameter
	0 mm	Outside diameter upper tolerance
	-0,032 mm	Outside diameter lower tolerance
H	28 mm	Height of the assembled bearing
h _i	28 mm	Height inner ring
	0,1 mm	Width upper tolerance
	-0,1 mm	Width lower tolerance
≈m	4,965 kg	Masa

Dimensions

D _i	270,8 mm	Inner diameter outer ring
D _M	270 mm	Rolling element pitch circle diameter
d _a	269,2 mm	Outer diameter inner ring
h	28 mm	Height of individual ring
	0 mm	Height of individual ring upper tolerance
	-0,025 mm	Height of individual ring lower tolerance
r _{min}	2 mm	Chamfer dimension
S	2 mm	Diameter of lubrication hole



25.08.2026, 06:40:26 UTC

SCHAEFFLER

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

	0,02 mm	Running accuracy, radial
	0,01 mm	Running accuracy, axial
S _{r min}	0,01 mm	Minimum radial bearing clearance, at standard bearing clearance
S _{r max}	0,03 mm	Maximum radial bearing clearance, at standard bearing clearance
S _{k min}	0,02 mm	Minimum axial tilting clearance, at standard bearing clearance
S _{k max}	0,06 mm	Maximum axial tilting clearance, at standard bearing clearance
RLO _{max}	0,005 mm	Low clearance: Radial clearance
RLO _{max}	0,01 mm	Low clearance: Preload
VSP _{min}	0,005 mm	Minimum bearing preload
VSP _{max}	0,025 mm	Maximum bearing preload
C _a	149.000 N	Basic dynamic load rating, axial
C _{0a}	600.000 N	Basic static load rating, axial
C _r	106.000 N	Basic dynamic load rating, radial (for radial load only)
C _{0r}	295.000 N	Basic static load rating, radial (for radial load only)
N _{G oil}	565 1/min	Limiting speed for oil lubrication with normal clearance
N _{G Grease}	280 1/min	Limiting speed for grease lubrication with normal clearance
N _{G oil}	280 1/min	Limiting speed for oil lubrication with preload
N _{G Grease}	140 1/min	Limiting speed for grease lubrication with preload

61848

Dimensions identical to ISO dimension series 18



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy