




FAG

T4EB240

Tapered roller bearing

Tapered roller bearings T, main dimensions
acc. to ISO 355, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	320 mm	Outside diameter
B	39 mm	Width, inner ring
C	30 mm	Width, outer ring
T	42 mm	Width, total
C _r	405.000 N	Basic dynamic load rating, radial
C _{0r}	730.000 N	Basic static load rating, radial
C _{ur}	81.000 N	Fatigue load limit, radial
n _G	2.070 1/min	Limiting speed
n _{gr}	1.230 1/min	Thermal speed rating
≈m	8,4 kg	Masa



Mounting dimensions

d _a max	255 mm	Maximum diameter of shaft shoulder
d _b min	259 mm	Minimum diameter of shaft shoulder
D _a min	299 mm	Minimum diameter of housing shoulder
D _a max	306 mm	Maximum diameter of housing shoulder
D _b min	310 mm	Minimum diameter of housing shoulder
C _a min	8 mm	Minimum axial space
C _b min	12 mm	Minimum axial space
r _a max	3 mm	Maximum fillet radius of shaft
r _b max	3 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	3 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	3 mm	Minimum chamfer dimension of outer ring back face
a	61 mm	Distance between the apexes of the pressure cones
d ₁	278 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,46	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,31	Dynamic axial load factor
Y ₀	0,72	Static axial load factor

Additional information

T4EB240	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia