




**TKLT25X4000-U-EWL-G4**

Profile rail

Guideways for linear ball bearing unit and four-row linear recirculating ball guidance system, for screw mounting from below

Informacje techniczne



Twoja aktualna wersja produktu

|                 |       |
|-----------------|-------|
| Size            | 25    |
| Length          | ~4000 |
| Guideway design | U     |
| Accuracy class  | G4    |

Main Dimensions & Performance Data

|       |          |                                  |
|-------|----------|----------------------------------|
| h     | 22 mm    | Height                           |
| b     | 23 mm    | Width rail                       |
| l max | 3.900 mm | Max length single piece guideway |
| ≈m    | 13,62 kg | Masa                             |



Mounting dimensions

|                    |         |                           |
|--------------------|---------|---------------------------|
| h <sub>1</sub>     | 12,3 mm | Length                    |
| G <sub>1</sub>     | M6      | Thread, DIN ISO 4762-12.9 |
| G1 M <sub>A</sub>  | 17 Nm   | Tightening torque         |
| j <sub>L</sub>     | 60 mm   | Increment                 |
| a <sub>L</sub> min | 10 mm   | Distance                  |
| a <sub>L</sub> max | 50 mm   | Distance                  |
| a <sub>R</sub> min | 10 mm   | Distance                  |
| a <sub>R</sub> max | 50 mm   | Distance                  |
| t <sub>7</sub>     | 12 mm   | Thread length             |
| K <sub>1</sub>     | M6      | Thread                    |
| K1 M <sub>A</sub>  | 16,5 Nm | Tightening torque         |

Additional information

|          |      |               |
|----------|------|---------------|
| VMKB_064 | TKLT | Material name |
|----------|------|---------------|