




TTUE70-XL

Take-up housing unit

Take-up housing units TTUE, cast iron housing, radial insert ball bearing with eccentric locking collar, T seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	70 mm	Bore diameter
---	-------	---------------

H	166 mm	Height
---	--------	--------

L	214 mm	Length total
---	--------	--------------

B 1	66 mm	Locking collar total width
-----	-------	----------------------------

≈m	6,82 kg	Masa
----	---------	------

Mounting dimensions

A 1	25 mm	Width guidance groove
-----	-------	-----------------------

H13		Width guidance groove clearance
-----	--	---------------------------------

H 1	151 mm	Distance guidance grooves
-----	--------	---------------------------

0,25 mm		Upper distance guidance groove tolerance
---------	--	--

-0,25 mm		Lower distance guidance groove tolerance
----------	--	--

N	41 mm	Fixing bore
---	-------	-------------



Dimensions

L 1	135 mm	Distance shaft axis
L 2	20 mm	Length fixed link
L 3	120 mm	Length guidance groove
A	70 mm	Width housing fixing side
N 1	35 mm	Width recess
N 2	70 mm	Height recess
S 1	44,5 mm	Distance of raceway to locking collar
T	110 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A 2	50 mm	Width housing

Additional information

TUE13/14	Housing
GE70-XL-KTT-B	Bearing designation

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.