




FAG

UCFL205-14

Flanged housing unit

Flanged housing unit UCFL

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|                 |           |                                   |
|-----------------|-----------|-----------------------------------|
| d               | 22,225 mm | Bore diameter                     |
| L               | 68 mm     | Flange width                      |
| H               | 130 mm    | Height flange                     |
| U               | 35,8 mm   | Total height unit                 |
| C <sub>r</sub>  | 14.900 N  | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 7.800 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 410 N     | Fatigue load limit, radial        |
| ≈m              | 0,67 kg   | Masa                              |

Mounting dimensions

|   |       |                          |
|---|-------|--------------------------|
| J | 99 mm | Distance fixing bore     |
| N | 16 mm | Fixing bore              |
| n | 2     | Number of screwing holes |



### Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 27 mm   | Height housing                    |
| A <sub>1</sub> | 15 mm   | Thickness of flange               |
| A <sub>2</sub> | 16 mm   | Distance raceway                  |
| B              | 34,1 mm | Width                             |
| Q              | M6      | Connection thread for lubrication |

### Additional information

|          |                     |
|----------|---------------------|
| 1        | Number of housings  |
| FL205    | Housing             |
| UC205-14 | Bearing designation |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |