



**FAG****UK208**

Radial insert ball bearing

Radial insert ball bearings UK, spherical outer ring, location by adapter sleeve, RSR seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

D _{SP}	80 mm	Outside diameter
B	31 mm	Width
C _{0r}	19.800 N	Basic static load rating, radial
C _{ur}	1.030 N	Fatigue load limit, radial
C _r	34.500 N	Basic dynamic load rating, radial
≈m	0,7 kg	Masa

Dimensions

C	21 mm	Width, outer ring
C ₂	21,6 mm	Sealing total width
C _a	6,2 mm	Distance to lubrication hole
d ₃	58 mm	Outside diameter locking collar/locknut
B ₂	10 mm	Width nut and lock

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	13,6	Calculation factor
----------------	------	--------------------



Additional information

H2308-J30QH	Adapter sleeve
KM8	Locknut
MB8	Fuse
H.H2308	Sleeve

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna