





FAG

UK217

Radial insert ball bearing

Radial insert ball bearings UK, spherical outer ring, location by adapter sleeve, RSR seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

D _{SP}	150 mm	Outside diameter
B	48 mm	Width
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	3.050 N	Fatigue load limit, radial
C _r	88.000 N	Basic dynamic load rating, radial
≈m	3,9 kg	Masa

Dimensions

C	35 mm	Width, outer ring
C ₂	36,4 mm	Sealing total width
C _a	10 mm	Distance to lubrication hole
d ₃	110 mm	Outside diameter locking collar/locknut
B ₂	18 mm	Width nut and lock

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	14,8	Calculation factor
----------------	------	--------------------



Additional information

H2317-J30QH	Adapter sleeve
KM17	Locknut
MB17	Fuse
H.H2317	Sleeve

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna