




FAG

UKT215

Take-up housing unit

Housing units UKT, cast iron housing, radial insert ball bearing with adapter sleeve, RSR seals, for linear motion

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	65 mm	Bore diameter
---	-------	---------------

H	167 mm	Height
---	--------	--------

L	232 mm	Length total
---	--------	--------------

B 1	73 mm	Locking collar total width
-----	-------	----------------------------

≈m	7,69 kg	Masa
----	---------	------

Mounting dimensions

A 1	26 mm	Width guidance groove
-----	-------	-----------------------

0,3 mm	Upper width guidance groove tolerance
--------	---------------------------------------

0 mm	Lower width guidance groove tolerance
------	---------------------------------------

H 1	151 mm	Distance guidance grooves
-----	--------	---------------------------

0 mm	Upper distance guidance groove tolerance
------	--

-0,8 mm	Lower distance guidance groove tolerance
---------	--

N	41 mm	Fixing bore
---	-------	-------------



Dimensions

L ₁	140 mm	Distance shaft axis
L ₂	21 mm	Length fixed link
L ₃	121 mm	Length guidance groove
A	70 mm	Width housing fixing side
N ₁	32 mm	Width recess
N ₂	70 mm	Height recess
T	111 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A ₂	48 mm	Width housing

Additional information

T215	Housing
UK215	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.