


VSA200414-N-ZT

Slewing ring, 4 point contact bearing, external gear teeth

Slewing ring, 4 point contact bearing, external gear teeth

Informacje techniczne



Twoja aktualna wersja produktu

Centering	ZT	Centering on inner and outer ring
Gearing	N	Normalized gear teeth on bearing ring
Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53

Main Dimensions & Performance Data

d _i	342 mm	Bore Diameter
	0,5 mm	Bore diameter upper tolerance
	0 mm	Bore diameter lower tolerance
d _{iZT}	344 mm	Diameter centring inner ring
	IT8	Diameter centring inner ring tolerance
H	56 mm	Height
D _a	503,3 mm	Outside Diameter
D _{iZT}	417 mm	Diameter centring outer ring
	IT8	Diameter centring outer ring tolerance
T	4,5 mm	Length centering outer ring
t	10 mm	Length centering inner ring
h _a	44,5 mm	Width outer ring
h _i	44,5 mm	Height of inner ring
≈m	31,4 kg	Masa



Dimensions

D _i	415,5 mm	Inner diameter outer ring
	0,5 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
d _a	412,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,5 mm	Outside diameter inner ring lower tolerance
n _i	24	Number of fixing holes in inner ring
L _i	368 mm	Pitchcircle diameter fixing holes inner ring
d _B	14 mm	Fixing bore
n _a	20	Number of fixing holes in outer ring
L _a	455 mm	Pitchcircle diameter fixing holes outer ring
d _{Ba}	M12	Tread fixing bore
G _i	20 mm	Thread depth fixing hole
F _{r zul}	76.000 N	Max. radial load fixing screws (friction locking)
d ₀	495 mm	Pitch circle diameter gearing
m	5 mm	Modul of gearing
z	99	Number of teeth
	-0,18 mm	Profile shift
b	40 mm	Width gearing
D	480 mm	Offset diameter outer ring
	0 mm	Offset diameter outer ring upper tolerance
	-0,5 mm	Offset diameter outer ring lower tolerance
F _{z norm}	15.900 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
F _{z max}	23.600 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)



Temperature range

T_{min}	-25 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.

Calculation factors

C_a	137.000 N	Basic dynamic load rating, axial
C_{0a}	660.000 N	Basic static load rating, axial
C_r	124.000 N	Basic dynamic load rating, radial
C_{0r}	305.000 N	Basic static load rating, radial

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Momenty względem wszystkich osi



Smarowanie smarem



Uszczelnienie dwustronne



Łożysko gabarytowe