


VSA200744-N

Slewing ring, 4 point contact bearing, external gear teeth

Slewing ring, 4 point contact bearing, external gear teeth

Informacje techniczne



Twoja aktualna wersja produktu

|                           |             |                                                                          |
|---------------------------|-------------|--------------------------------------------------------------------------|
| Gearing                   | N           | Normalized gear teeth on bearing ring                                    |
| Radial internal clearance | Standard_SL | Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53 |

Main Dimensions & Performance Data

|             |          |                               |
|-------------|----------|-------------------------------|
| $d_i$       | 672 mm   | Bore Diameter                 |
|             | 0,6 mm   | Bore diameter upper tolerance |
|             | 0 mm     | Bore diameter lower tolerance |
| H           | 56 mm    | Height                        |
| $D_a$       | 838,1 mm | Outside Diameter              |
| $h_a$       | 44,5 mm  | Width outer ring              |
| $h_i$       | 44,5 mm  | Height of inner ring          |
| $\approx m$ | 61,83 kg | Masa                          |



Dimensions

|                     |           |                                                                     |
|---------------------|-----------|---------------------------------------------------------------------|
| D <sub>i</sub>      | 745,5 mm  | Inner diameter outer ring                                           |
|                     | 0,6 mm    | Inner diameter outer ring upper tolerance                           |
|                     | 0 mm      | Inner diameter outer ring lower tolerance                           |
| d <sub>a</sub>      | 742,5 mm  | Outside diameter inner ring                                         |
|                     | 0 mm      | Outside diameter inner ring upper tolerance                         |
|                     | -0,6 mm   | Outside diameter inner ring lower tolerance                         |
| n <sub>i</sub>      | 40        | Number of fixing holes in inner ring                                |
| L <sub>i</sub>      | 698 mm    | Pitchcircle diameter fixing holes inner ring                        |
| d <sub>B</sub>      | 14 mm     | Fixing bore                                                         |
| n <sub>a</sub>      | 36        | Number of fixing holes in outer ring                                |
| L <sub>a</sub>      | 785 mm    | Pitchcircle diameter fixing holes outer ring                        |
| d <sub>Ba</sub>     | M12       | Tread fixing bore                                                   |
| G <sub>i</sub>      | 20 mm     | Thread depth fixing hole                                            |
| F <sub>r zul</sub>  | 148.700 N | Max. radial load fixing screws (friction locking)                   |
| d <sub>0</sub>      | 828 mm    | Pitch circle diameter gearing                                       |
| m                   | 6 mm      | Modul of gearing                                                    |
| z                   | 138       | Number of teeth                                                     |
|                     | -0,158 mm | Profile shift                                                       |
| F <sub>z norm</sub> | 21.300 N  | Max. tooth force root fatigue strenght (at a shock factor of 1,2)   |
| F <sub>z max</sub>  | 31.500 N  | Max. tooth force against tooth fracture (at a shock factor of 1,35) |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -25 °C | Operating temperature min. |
| T <sub>max</sub> | 80 °C  | Operating temperature max. |



### Calculation factors

|          |             |                                   |
|----------|-------------|-----------------------------------|
| $C_a$    | 171.000 N   | Basic dynamic load rating, axial  |
| $C_{0a}$ | 1.200.000 N | Basic static load rating, axial   |
| $C_r$    | 155.000 N   | Basic dynamic load rating, radial |
| $C_{0r}$ | 550.000 N   | Basic static load rating, radial  |

### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Momenty względem wszystkich osi



Smarowanie smarem



Uszczelnienie dwustronne



Łożysko gabarytowe