


VSI200544-N

Slewing ring, 4 point contact bearing, internal gear teeth

Slewing ring, 4 point contact bearing, internal gear teeth

Informacje techniczne



Twoja aktualna wersja produktu

Gearing	N	Normalized gear teeth on bearing ring
Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53

Main Dimensions & Performance Data

d ₁	444 mm	Bore Diameter
T	4,5 mm	Length centering inner ring
H	56 mm	Height
D _a	616 mm	Outside Diameter
	-0,5 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
h _a	44,5 mm	Width outer ring
h _i	44,5 mm	Width inner ring
≈m	41,3 kg	Masa



Dimensions

D _i	545,5 mm	Inner diameter outer ring
	0,5 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
L _a	590 mm	Pitchcircle diameter fixing holes outer ring
n _a	32	Number of fixing holes in outer ring
d _B	14 mm	Fixing bore
d _a	542,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,5 mm	Outside diameter inner ring lower tolerance
L _i	505 mm	Pitchcircle diameter fixing holes inner ring
d _{Bi}	M12	Tread fixing bore
G _I	20 mm	Thread depth fixing hole
n _i	32	Number of fixing holes in inner ring
F _{r zul}	132.200 N	Max. radial load fixing screws (friction locking)
m	6 mm	Modul of gearing
z	76	Number of teeth
d ₀	456 mm	Pitch circle diameter gearing
F _{z norm}	23.700 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)

F _{z max}	35.000 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)
--------------------	----------	---

Temperature range

T _{min}	-25 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.



Calculation factors

C _a	152.000 N	Basic dynamic load rating, axial
C _{0a}	870.000 N	Basic static load rating, axial
C _r	138.000 N	Basic dynamic load rating, radial
C _{0r}	400.000 N	Basic static load rating, radial

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Momenty względem wszystkich osi
- 

Smarowanie smarem
- 

Uszczelnienie dwustronne
- 

Łożysko gabarytowe