


VU250433

Slewing ring, 4 point contact bearing, without gear teeth

Four point contact bearings without gear teeth, sealed on both sides

Informacje techniczne



Main Dimensions & Performance Data

d _i	344 mm	Inner diameter inner ring
	0,5 mm	Inner diameter inner ring lower tolerance
	0,5 mm	Inner diameter inner ring upper tolerance
H	55 mm	Height
D _a	522 mm	Outside Diameter
	0,8 mm	Outside diameter lower tolerance
	0,8 mm	Outside diameter upper tolerance
h _a	50 mm	Width outer ring
h _i	50 mm	Width inner ring
	0,06 mm	Normal radial clearance min.
	0,25 mm	Normal radial clearance max.
	0,11 mm	Normal axial clearance min.
	0,41 mm	Normal axial clearance max.
≈m	41,023 kg	Masa



Dimensions

D _i	432 mm	Inner diameter outer ring
d _a	434 mm	Outside diameter inner ring
d _B	18 mm	Fixing bore
L _a	490 mm	Pitchcircle diameter fixing holes outer ring
n _a	20	Number of fixing holes in outer ring
L _i	376 mm	Pitchcircle diameter fixing holes inner ring
n _i	20	Number of fixing holes in inner ring
F _{r zul}	156.000 N	Max. radial load fixing screws (friction locking)

Temperature range

T _{min}	-25 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Calculation factors

C _a	315.000 N	Basic dynamic load rating, axial
C _{0a}	910.000 N	Basic static load rating, axial
C _r	285.000 N	Basic dynamic load rating, radial (for radial load only)
C _{0r}	415.000 N	Basic static load rating, radial (for radial load only)

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Momenty względem wszystkich osi
	Smarowanie smarem
	Uszczelnienie dwustronne
	Łożysko gabarytowe