


XSI140944-N

Slewing ring, crossed roller bearing, internal gear teeth

Crossed roller bearings, standard series 14,
internal gear teeth, lip seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Gearing N Normalized gear teeth on bearing ring

Main Dimensions & Performance Data

d i	840 mm	Bore Diameter
d a ZT	941 mm	Diameter centring inner ring
	-IT7	Diameter centring inner ring tolerance
t	4,5 mm	Length centering inner ring
D a ZT	1.014 mm	Diameter centring outer ring
	-IT7	Diameter centring outer ring tolerance
T	10 mm	Length centering outer ring
H	56 mm	Height
≈m	74,1 kg	Masa



Dimensions

D _i	945 mm	Inner diameter outer ring
	0,7 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
h _a	44,5 mm	Width outer ring
L _a	990 mm	Pitchcircle diameter fixing holes outer ring
n _a	44	Number of fixing holes in outer ring
d _B	14 mm	Fixing bore
	44,5 mm	Width inner ring
L _i	905 mm	Pitchcircle diameter fixing holes inner ring
n _i	44	Number of fixing holes in inner ring
	M12	Tread fixing bore
t _G	20 mm	Thread depth oil connector
b	44,5 mm	Width gearing
m	8 mm	Modul of gearing
z	107	Number of teeth
d ₀	856 mm	Pitch circle diameter gearing
F _{z norm}	31.400 N	Max. tooth force root fatigue strenght
F _{z max}	46.700 N	Max. tooth force against tooth fracture
	0,06 mm	Running accuracy
	0,06 mm	Running accuracy
	0,11 mm	Running accuracy
	0,09 mm	Running accuracy

Temperature range

T _{min}	-25 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.



Calculation factors

C_a	315.000 N	Basic dynamic load rating, axial
C_{0a}	1.240.000 N	Basic static load rating, axial
C_r	223.000 N	Basic dynamic load rating, radial (for radial load only)
C_{0r}	610.000 N	Basic static load rating, radial (for radial load only)
VSP max	0,05 mm	Maximum bearing preload
VSP min	0,01 mm	Min. bearing preload
$F_{r\text{ zul}}$	181.700 N	Max. radial load fixing screws (friction locking)

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Momenty względem wszystkich osi
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Łożysko gabarytowe