



25.08.2026, 00:45:48 UTC

SCHAEFFLER




Axial/radial roller bearing

Axial/radial bearings, double direction, for screw mounting



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Angular measuring system integrated	No
-------------------------------------	----

Main Dimensions & Performance Data

d	260 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,018 mm	Bore diameter lower tolerance
D	385 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,02 mm	Outside diameter lower tolerance
H	55 mm	Height
C _r	140.000 N	Basic dynamic load rating, radial
C _{0r}	355.000 N	Basic static load rating, radial
C _a	168.000 N	Basic dynamic load rating, axial
C _{0a}	1.090.000 N	Basic static load rating, axial
n _G	300 1/min	Limiting speed
M _R	9 Nm	Bearing friction torque at 5 1/min
≈m	17,5 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje



Mounting dimensions

J	280 mm	Pitch circle diameter fixing holes in inner ring
J 1	365 mm	Pitch circle diameter fixing holes in outer ring
d 1	9,3 mm	Fixing holes diameter inner ring
d 2	15 mm	Counterbore diameter of fixing holes
a	8,2 mm	Counterbore depth of fixing holes
	34	Quantity of fixing holes inner ring
d 3	9,3 mm	Fixing holes diameter outer ring
	33	Quantity of fixing holes outer ring
n	36	Pitch quantity
t	10 °	Pitch separation angle
G	M12	Threaded extraction hole
	3	Quantity of threaded extraction hole
M A	34 Nm	Screw tightening torque
	2	Quantity of retaining screws
t 1	6 µm	Axial and radial runout, measurement standard; Measured on mounted bearing, with ideal adjacent construction.

Dimensions

H 1	36,5 mm	Height contact face outer ring
	0,04 mm	Height contact face outerring H1 upper tolerance
	-0,04 mm	Height contact face outerring H1 lower tolerance
H 2	18,5 mm	Height contact face outer ring
	0,025 mm	Height contact face outerring H2 upper tolerance
	-0,025 mm	Height contact face outerring H2 lower tolerance
D 1 max	347 mm	Maximum diameter inner ring
C	18 mm	Width of outer ring



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	13.800 N/μm	Axial rigidity of bearing position
c _{rL}	7.400 N/μm	Radial rigidity of bearing position
c _{kL}	166.000 Nm/mrad	Tilting rigidity of bearing position
c _{aW}	19.000 N/μm	Axial rigidity of rolling element set
c _{rW}	8.100 N/μm	Radial rigidity of rolling element set
c _{kW}	265.000 Nm/mrad	Tilting rigidity of rolling element set

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Momenty względem wszystkich osi
-  Smarowanie smarem
-  Bez uszczelnienia
-  Łożysko gabarytowe