**ZARF3590-TV**

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARF, double direction, for screw mounting

Informacje techniczne

Twoja aktualna wersja produktu





Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------


Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	90 mm	Outside diameter
H	54 mm	Height
C _a	56.000 N	Basic dynamic load rating, axial
C _{0a}	148.000 N	Basic static load rating, axial
C _r	26.000 N	Basic dynamic load rating, radial
C _{0r}	47.000 N	Basic static load rating, radial
C _{ua}	12.900 N	Fatigue load limit, axial
C _{ur}	6.800 N	Fatigue load limit, radial
n _{G Oil}	4.800 1/min	Limiting speed for oil lubrication
n _{G Grease}	1.700 1/min	Limiting speed for grease lubrication
M _{RL}	0,9 Nm	Bearing friction torque
≈m	1,036 kg	Masa

Mounting dimensions

D _{a max}	61 mm	Maximum diameter of housing shoulder
d _{a min}	50 mm	Minimum diameter shaft shoulder
t ₁	0,1 mm	Position bore in the housing





Dimensions

H 1	35 mm	Height outer ring over wave washer
C	18 mm	Width, outer ring
C 1	10 mm	Distance to lubrication hole
D 1	60 mm	Rip diameter shaft washer
B	11 mm	Width inner ring
r min	0,3 mm	Minimum chamfer dimension
r 1 min	0,6 mm	Minimum chamfer dimension
d 1	3,2 mm	Diameter lubrication hole
J	73 mm	Pitch circle diameter (holes)
n	12	Number of screwing holes
n x t	30 °	Split

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.



Additional information

c_{aL}	2.600 N/ μ m	Rigidity axial
c_{kL}	740 Nm/mrad	Tilting stiffness
M_m	2,8 kg*cm2	Mass moment of inertia
	1 μ m	Axial runout
radial	ZMA35/58	Recommended INA precision locknut for radial locking (not included)
axial	AM35/58	Recommended INA precision locknut for axial locking (not included)
M_A	40 Nm	Tightening torque nut
	12.143 N	Required locknut force
	M6	Screw size
n_a	12	Number of screws
na x ta	30 °	Division (screwing holes)

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia