


**ZARN55115-L-TV**

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARN...-L, double direction, long shaft
locating washer

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	115 mm	Outside diameter
H	103 mm	Hight
C _a	177.000 N	Basic dynamic load rating, axial
C _{0a}	500.000 N	Basic static load rating, axial
C _r	44.000 N	Basic dynamic load rating, radial
C _{0r}	98.000 N	Basic static load rating, radial
C _{ua}	46.500 N	Fatigue load limit, axial
C _{ur}	13.800 N	Fatigue load limit, radial
n _{G Oil}	2.900 1/min	Limiting speed for oil lubrication
n _{G Grease}	1.000 1/min	Limiting speed for grease lubrication
M _{RL}	4 Nm	Bearing friction torque
≈m	3,945 kg	Masa

Mounting dimensions

D _{a max}	101 mm	Maximum diameter of housing shoulder
d _{a min}	78 mm	Minimum diameter shaft shoulder



Dimensions

H 1	74,5 mm	Height outer ring over wave washer
C	25 mm	Width, outer ring
D 1	100 mm	Rip diameter shaft washer
D 2	80 mm	Heeldiameter wave washer long
D 3	98 mm	Outside diameter wave washer long
B	17,5 mm	Width, inner ring
B 1	38,5 mm	Width wave washer long
B 2	18 mm	Width heel wave washer long
r min	0,3 mm	Minimum chamfer dimension
r 1 min	0,6 mm	Minimum chamfer dimension

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Additional information

c aL	4.900 N/μm	Rigidity axial
c kL	3.600 Nm/mrad	Tilting stiffness
M m	43 kg*cm2	Mass moment of inertia
	1 μm	Axial runout
radial	ZMA55/98	Recommended INA precision locknut for radial locking (not included)
axial	AM55	Recommended INA precision locknut for axial locking (not included)
M A	220 Nm	Tightening torque nut
	39.807 N	Required locknut force
	80X100X10	Rotary shaft seal to DIN 3760 (not included)



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia