




ZARN70130-TV

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARN, double direction

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	130 mm	Outside diameter
H	82 mm	Hight
C _a	201.000 N	Basic dynamic load rating, axial
C _{0a}	630.000 N	Basic static load rating, axial
C _r	56.000 N	Basic dynamic load rating, radial
C _{0r}	119.000 N	Basic static load rating, radial
C _{ua}	58.000 N	Fatigue load limit, axial
C _{ur}	16.100 N	Fatigue load limit, radial
n _{G Oil}	2.400 1/min	Limiting speed for oil lubrication
n _{G Grease}	800 1/min	Limiting speed for grease lubrication
M _{RL}	4,8 Nm	Bearing friction torque
≈m	4,124 kg	Masa

Mounting dimensions

D _{a max}	116 mm	Maximum diameter of housing shoulder
d _{a min}	100 mm	Minimum diameter shaft shoulder



Dimensions

H ₁	53,5 mm	Height outer ring over wave washer
C	25 mm	Width, outer ring
D ₁	115 mm	Rip diameter shaft washer
B	17,5 mm	Width, inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	5.800 N/μm	Rigidity axial
c _{kL}	6.000 Nm/mrad	Tilting stiffness
M _m	62,2 kg*cm2	Mass moment of inertia
	1 μm	Axial runout
radial	ZMA70/110	Recommended INA precision locknut for radial locking (not included)
axial	AM70	Recommended INA precision locknut for axial locking (not included)
M _A	330 Nm	Tightening torque nut
	46.786 N	Preload force axial



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia