




ZKLFA1050-2RS

Axial angular contact ball bearing

Angular contact ball bearing units
ZKLFA..-2RS, double direction, for screw
mounting, lip seals on both sides, with
flattened flange

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RS	Contact lip seal on both sides
---------	-----	--------------------------------

Main Dimensions & Performance Data

d	10 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	32 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	20 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	13.400 N	Basic dynamic load rating, axial
C _{0a}	18.800 N	Basic static load rating, axial
C _{ua}	850 N	Fatigue load limit, axial
n _G Grease	10.900 1/min	Limiting speed for grease lubrication
n _g	4.600 1/min	Thermally permissible speed
≈m	0,124 kg	Masa



25.08.2026, 03:14:50 UTC

SCHAEFFLER



Dimensions

Temperature range

Additional information

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne