




ZKLN0624-2RS-PE

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2RS-PE, Increased tolerances,
double direction, lip seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RS	Contact lip seals on both sides
Tolerance class	PE	Less stringent bearing design

Main Dimensions & Performance Data

d	6 mm	Bore diameter
	0,003 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	24 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	15 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	6.900 N	Basic dynamic load rating, axial
C _{0a}	8.500 N	Basic static load rating, axial
C _{ua}	385 N	Fatigue load limit, axial
n _G Grease	16.400 1/min	Limiting speed for grease lubrication
n _g	6.800 1/min	Thermally safe operating speed
M _R	0,04 Nm	Bearing frictional torque
≈m	0,04 kg	Masa



Mounting dimensions

D a max	19 mm	Maximum diameter of housing
---------	-------	-----------------------------

d a min	9 mm	Minimum diameter shaft
---------	------	------------------------

Dimensions

d 1	14 mm	Rib diameter inner ring
-----	-------	-------------------------

r min	0,3 mm	Minimum chamfer dimension
-------	--------	---------------------------

r 1 min	0,6 mm	Minimum chamfer dimension
---------	--------	---------------------------

α	60 °	Contact angle
---	------	---------------

Temperature range

T min	-30 °C	Operating temperature min.
-------	--------	----------------------------

T max	120 °C	Operating temperature max.
-------	--------	----------------------------

Additional information

c aL	200 N/μm	Rigidity axial
------	----------	----------------

c kL	8 Nm/mrad	Tilting rigidity
------	-----------	------------------

M m	0,004 kg*cm2	Mass moment of inertia
-----	--------------	------------------------

	5 μm	Axial runout
--	------	--------------

	ZM06	Recommended INA precision locknut for radial locking
--	------	--

M A	2 Nm	Tightening torque for the recommended INA precision locknut
-----	------	---

	2.404 N	Required locknut force axial
--	---------	------------------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne