


**ZKLN2052-2Z-XL**

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...2Z, double direction, gap seals on
both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	20 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	52 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	28 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	28.500 N	Basic dynamic load rating, axial
C _{0a}	47.000 N	Basic static load rating, axial
C _{ua}	2.850 N	Fatigue load limit, axial
n _G Grease	8.700 1/min	Limiting speed for grease lubrication
n _g	5.400 1/min	Thermally safe operating speed
M _R	0,15 Nm	Bearing frictional torque
≈m	0,311 kg	Masa



Mounting dimensions

D _a max	43 mm	Maximum diameter of housing
d _a min	25 mm	Minimum diameter shaft

Dimensions

d ₁	34,5 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	650 N/μm	Rigidity axial
c _{kL}	140 Nm/mrad	Tilting rigidity
M _m	0,273 kg*cm2	Mass moment of inertia
	2 μm	Axial runout
	ZM20	Recommended INA precision locknut for radial locking
	AM20	Recommended INA precision locknut for axial locking
M _A	18 Nm	Tightening torque for the recommended INA precision locknut
	8.258 N	Required locknut force axial



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne