


ZKLN4090-2Z-2AP-XL

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2Z-2AP-XL, matched pair, double
direction, gap seals on both sides



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	
Number of bearings	2AP	Axial angular contact ball bearings, matched pair



Main Dimensions & Performance Data

d	40 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	90 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	92 mm	Width
	0 mm	Width upper tolerance
	-0,5 mm	Width lower tolerance
C _a	129.000 N	Basic dynamic load rating, axial
C _{0a}	300.000 N	Basic static load rating, axial
C _{ua}	18.100 N	Fatigue load limit, axial
n _G Grease	4.400 1/min	Limiting speed for grease lubrication
n _g	3.100 1/min	Thermally safe operating speed
≈m	2,68 kg	Masa

Mounting dimensions

D _{a max}	80 mm	Maximum diameter of housing
d _{a min}	56 mm	Minimum diameter shaft

Dimensions

d ₁	65 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

	2,5 μm	Axial runout
	ZMA40/62	Recommended INA precision locknut for radial locking
	AM40	Recommended INA precision locknut for axial locking
M_A	110 Nm	Tightening torque for the recommended INA precision locknut
	25.185 N	Required locknut force axial

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne