




ZKLN60110-2Z-XL

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2Z, double direction, gap seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	60 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,008 mm	Bore diameter lower tolerance
D	110 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,015 mm	Outside diameter lower tolerance
B	45 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	93.000 N	Basic dynamic load rating, axial
C _{0a}	214.000 N	Basic static load rating, axial
C _{ua}	13.000 N	Fatigue load limit, axial
n _G Grease	4.000 1/min	Limiting speed for grease lubrication
n _g	3.000 1/min	Thermally safe operating speed
M _R	1 Nm	Bearing frictional torque
≈m	1,8 kg	Masa



Mounting dimensions

D _a max	100 mm	Maximum diameter of housing
d _a min	82 mm	Minimum diameter shaft

Dimensions

d ₁	85 mm	Rib diameter inner ring
r _{min}	0,6 mm	Minimum chamfer dimension
r ₁ min	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	1.300 N/μm	Rigidity axial
c _{kL}	1.650 Nm/mrad	Tilting rigidity
M _m	13,7 kg*cm2	Mass moment of inertia
	3 μm	Axial runout
	ZMA60/98	Recommended INA precision locknut for radial locking
	AM60	Recommended INA precision locknut for axial locking
M _A	100 Nm	Tightening torque for the recommended INA precision locknut
	16.700 N	Required locknut force axial



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne